SIMONSWERK

VARIANT® VN

VN 3748/160

as retrofit hinge for unrebated heavy-duty doors with steel frames

hinge	
-------	--

Technical details

load capacity	160,0 kg
knuckle length	160,0 mm
knuckle diameter	22,5 mm
material thickness	3,5 mm
cutter diameter	24,0 mm
screws	5,0 x 50,0 mm
pin diameter	10,0 mm



SIMONSWERK VARIANT heavy duty hinge VN 3748/160 for unrebated doors for retrofitting on steel frames with M 10 blind rivet nuts. CE certified, load capacity 160 kg, knuckle length 160 mm, knuckle diameter 22,5 mm, right hand and left hand applicable. Internal torsion-proof screw pin, concealed, maintenance-free, generously dimensioned axial-radial slide bearings. Finish...

Note

The load capacity mentioned above refers to the use of 2 hinges per door leaf (1×2 m).

Also available with security pin (MSTS).

A reinforcing dowel 12x50 mm per hinge is recommended when the door is subject to heavy usage.

Product features

- for unrebated heavy-duty doors
- for casing and steel frame
- for blind rivet nut
- internal torsion-proof screw pin
- concealed, maintenance -free axial-radial slide bearings

Functional areas


fire resistance, smoke resistance

Quality marks

Combination

accessories blind rivet nut M 10





SIMONSWERK VARIANT® VN

VN 3748/160

as retrofit hinge for unrebated heavy-duty doors with steel frames

hinge

installation tools

universal milling frame plug-on drilling jig VARIANT VN 3700/160

serial drilling jig VARIANT VN 3700/160 template 5 250353 5

Items (DIN reference: DIN right and left hand)

	,
finish(es)	galvanised 010
packing unit item number	pack of 2 5 050541 0 01002
finish(es)	satin nickelled/F2 018
packing unit item number	pack of 2 5 050541 0 01802
finish(es) packing unit	satin chromed/F1 037 pack of 2
item number	5 050541 0 03702
finish(es)	satin brushed stainless steel 040
packing unit item number	pack of 2 5 050541 0 04002

