

SIMONSWERK

VARIANT® VN

MULTI 3D VN 3130

for rebated timber doors with steel and concrete frames

hinge

Technical details

| | |
|------------------|----------|
| load capacity | 100,0 kg |
| knuckle length | 100,0 mm |
| knuckle diameter | 20,0 mm |

descriptive text

SIMONSWERK MULTI 3D VN 3130 door hinge with angular bolting for high pull-out strength for rebated doors with steel and concrete frames with overlap thickness of 13,0-18,0 mm. Frame mounting for threaded hole or heavy-duty fixing dowel. Load capacity 100 kg, knuckle length 100 mm, knuckle diameter 20 mm, right hand and left hand applicable. Three-dimensionally, continuously adjustable: Side +/- 3,0 mm, height +/- 4,0 mm, compression +/- 3,0 mm. Finish...

Note

The load capacity mentioned above refers to the use of 2 hinges per door leaf (1 x 2 m).

Also available with security pin (MSTS).

Product features

- for rebated doors
- for steel and concrete frames
- for overlap thicknesses 13-18 mm
- continuously 3D adjustable (side +/- 3,0 mm, height +/- 4,0 mm, compression +/- 3,0 mm)
- with angular bolting for high pull-out strength

Items (DIN reference: DIN right and left hand)

| | |
|--------------|------------------------------|
| finish(es) | satin nickelled 017 |
| packing unit | pack of 2 |
| item number | 5 030816 0 01702 |
| finish(es) | traffic white - RAL 9016 070 |
| packing unit | pack of 2 |
| item number | 5 030816 0 07002 |

